

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	2K PRIMER ACTIVATOR
Registration number	-
Synonyms	None.
Product code	2KPA-QT
Issue date	28-March-2015
Version number	01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Automotive Refinish Hardener/Activator
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name	Quest Automotive Products	
Address	600 Nova Drive SE Massillon, OH 44646 United States	
Division	Massillon	
Telephone	General Assistance	(330) 830-6000
e-mail	rpandrus@quest-ap.com	
Contact person	Not available.	

1.4. Emergency telephone number	CHEMTREC	(800) 424-9300
--	----------	----------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification F;R11, Repr. Cat. 3;R63, Xn;R48/20, Xi;R38, R67

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 2	H225 - Highly flammable liquid and vapour.
-------------------	------------	--

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Reproductive toxicity (the unborn child)	Category 2	H361d - Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure	Category 2	H373 - May cause damage to organs through prolonged or repeated exposure.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 2	H411 - Toxic to aquatic life with long lasting effects.
--	------------	---

Hazard summary

Physical hazards	Highly flammable.
Health hazards	Irritating to skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Vapours may cause drowsiness and dizziness. Occupational exposure to the substance or mixture may cause adverse health effects.

Environmental hazards	Not classified for hazards to the environment.
Specific hazards	Prolonged exposure may cause chronic effects.
Main symptoms	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: n-Butyl acetate, Toluene

Hazard pictograms



Signal word Danger

Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe mist or vapour.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor if you feel unwell.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use appropriate media to extinguish.
P391	Collect spillage.

Storage

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Supplemental label information 55 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment. EUH208 - Contains 1,6-Diisocyanatohexane. May produce an allergic reaction.

2.3. Other hazards None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
1-Methoxy-2-propyl acetate	20 - < 30	108-65-6 203-603-9	-	607-195-00-7	#
Classification:	DSD: R10				
	CLP: -				
Toluene	20 - < 30	108-88-3 203-625-9	-	601-021-00-3	#
Classification:	DSD: F;R11, Repr. Cat. 3;R63, Xn;R65-48/20, Xi;R38, R67				
	CLP: -				
n-Butyl acetate	10 - < 20	123-86-4 204-658-1	-	607-025-00-1	
Classification:	DSD: R10, R66-67				
	CLP: -				
Xylene	3 - < 5	1330-20-7 215-535-7	-	601-022-00-9	#
Classification:	DSD: R10, Xn;R20/21, Xi;R38				C
	CLP: -				C
Ethyl benzene	< 1	100-41-4 202-849-4	-	601-023-00-4	#
Classification:	DSD: F;R11, Xn;R20				
	CLP: -				
1,6-Diisocyanato-hexane	< 0,2	822-06-0 212-485-8	-	615-011-00-1	
Classification:	DSD: T;R23, Xi;R36/37/38, R42/43				2
	CLP: -				2

Other components below reportable levels 30 - < 40

List of abbreviations and symbols that may be used above

CLP: Regulation No. 1272/2008.

DSD: Directive 67/548/EEC.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

Composition comments

The full text for all R- and H-phrases is displayed in section 16.

SECTION 4: First aid measures

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Highly flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing media Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8.

For emergency responders Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up.

6.2. Environmental precautions Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil etc) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections For personal protection, see section 8. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapour. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	Ceiling	0,035 mg/m ³
	MAK	0,005 ppm 0,035 mg/m ³
1-Methoxy-2-propyl acetate (CAS 108-65-6)	Ceiling	0,005 ppm 550 mg/m ³
	MAK	100 ppm 275 mg/m ³
Ethyl benzene (CAS 100-41-4)	Ceiling	50 ppm 880 mg/m ³
	MAK	200 ppm 440 mg/m ³
n-Butyl acetate (CAS 123-86-4)	Ceiling	100 ppm 480 mg/m ³
	MAK	100 ppm 480 mg/m ³
Toluene (CAS 108-88-3)	MAK	100 ppm 190 mg/m ³
	STEL	50 ppm 380 mg/m ³
Xylene (CAS 1330-20-7)	MAK	100 ppm 221 mg/m ³
	STEL	50 ppm 442 mg/m ³

Belgium. Exposure Limit Values.

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	TWA	0,034 mg/m ³
	STEL	0,005 ppm 550 mg/m ³
1-Methoxy-2-propyl acetate (CAS 108-65-6)	TWA	100 ppm 275 mg/m ³
	STEL	50 ppm 551 mg/m ³
Ethyl benzene (CAS 100-41-4)	TWA	125 ppm 442 mg/m ³
	STEL	100 ppm 964 mg/m ³
n-Butyl acetate (CAS 123-86-4)	TWA	200 ppm 723 mg/m ³
	STEL	150 ppm 384 mg/m ³
Toluene (CAS 108-88-3)	TWA	100 ppm 77 mg/m ³
	STEL	20 ppm 442 mg/m ³
Xylene (CAS 1330-20-7)	TWA	100 ppm 221 mg/m ³
	STEL	50 ppm

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	TWA	0,1 mg/m3
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	550 mg/m3
	TWA	100 ppm 275 mg/m3 50 ppm
Ethyl benzene (CAS 100-41-4)	STEL	545 mg/m3
	TWA	435 mg/m3
n-Butyl acetate (CAS 123-86-4)	STEL	950 mg/m3
	TWA	710 mg/m3
Toluene (CAS 108-88-3)	STEL	384 mg/m3
	TWA	100 ppm 192 mg/m3 50 ppm
Xylene (CAS 1330-20-7)	STEL	442 mg/m3
	TWA	100 ppm 221 mg/m3 50 ppm

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
1-Methoxy-2-propyl acetate (CAS 108-65-6)	MAC	275 mg/m3
	STEL	50 ppm 550 mg/m3 100 ppm
Ethyl benzene (CAS 100-41-4)	MAC	442 mg/m3
	STEL	100 ppm 884 mg/m3 200 ppm
n-Butyl acetate (CAS 123-86-4)	MAC	724 mg/m3
	STEL	150 ppm 966 mg/m3 200 ppm
Toluene (CAS 108-88-3)	MAC	192 mg/m3
	STEL	50 ppm 384 mg/m3 100 ppm
Xylene (CAS 1330-20-7)	MAC	221 mg/m3
	STEL	50 ppm 442 mg/m3 100 ppm

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Type	Value
n-Butyl acetate (CAS 123-86-4)	TWA	710 mg/m3
		150 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	Ceiling	0,07 mg/m3
	TWA	0,035 mg/m3
1-Methoxy-2-propyl acetate (CAS 108-65-6)	Ceiling	550 mg/m3
	TWA	270 mg/m3
Ethyl benzene (CAS 100-41-4)	Ceiling	500 mg/m3
	TWA	200 mg/m3

Czech Republic. OELs. Government Decree 361

Components	Type	Value
n-Butyl acetate (CAS 123-86-4)	Ceiling	1200 mg/m3
	TWA	950 mg/m3
Toluene (CAS 108-88-3)	Ceiling	500 mg/m3
	TWA	200 mg/m3
Xylene (CAS 1330-20-7)	Ceiling	400 mg/m3
	TWA	200 mg/m3

Denmark. Exposure Limit Values

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	TLV	0,035 mg/m3
		0,005 ppm
1-Methoxy-2-propyl acetate (CAS 108-65-6)	TLV	275 mg/m3
		50 ppm
Ethyl benzene (CAS 100-41-4)	TLV	217 mg/m3
		50 ppm
n-Butyl acetate (CAS 123-86-4)	TLV	710 mg/m3
		150 ppm
Toluene (CAS 108-88-3)	TLV	94 mg/m3
		25 ppm
Xylene (CAS 1330-20-7)	TLV	109 mg/m3
		25 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	TWA	0,03 mg/m3
		0,005 ppm
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
	TWA	275 mg/m3
		50 ppm
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m3
		200 ppm
	TWA	442 mg/m3
		100 ppm
n-Butyl acetate (CAS 123-86-4)	STEL	700 mg/m3
		150 ppm
	TWA	500 mg/m3
		100 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m3
		100 ppm
	TWA	192 mg/m3
		50 ppm
Xylene (CAS 1330-20-7)	STEL	450 mg/m3
		100 ppm
	TWA	200 mg/m3
		50 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of September 2001)

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	Ceiling	0,07 mg/m3
		0,01 ppm

Finland. Workplace Exposure Limits

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	STEL	0,035 mg/m3
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	550 mg/m3
	TWA	100 ppm 270 mg/m3 50 ppm
Ethyl benzene (CAS 100-41-4)	STEL	880 mg/m3
	TWA	200 ppm 220 mg/m3 50 ppm
n-Butyl acetate (CAS 123-86-4)	STEL	960 mg/m3
	TWA	200 ppm 720 mg/m3 150 ppm
Toluene (CAS 108-88-3)	STEL	380 mg/m3
	TWA	100 ppm 81 mg/m3 25 ppm
Xylene (CAS 1330-20-7)	STEL	440 mg/m3
	TWA	100 ppm 220 mg/m3 50 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	VLE	0,15 mg/m3
	VME	0,02 ppm 0,075 mg/m3 0,01 ppm
1-Methoxy-2-propyl acetate (CAS 108-65-6)	VLE	550 mg/m3
	VME	110 ppm 275 mg/m3 50 ppm
Ethyl benzene (CAS 100-41-4)	VLE	442 mg/m3
	VME	100 ppm 88,4 mg/m3 20 ppm
homopolymer of HDI (CAS 28182-81-2)	VLE	1 mg/m3
n-Butyl acetate (CAS 123-86-4)	VLE	940 mg/m3
	VME	200 ppm 710 mg/m3 150 ppm
Toluene (CAS 108-88-3)	VLE	384 mg/m3
	VME	100 ppm 76,8 mg/m3 20 ppm
Xylene (CAS 1330-20-7)	VLE	442 mg/m3
	VME	100 ppm 221 mg/m3 50 ppm

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value	Form
1,6-Diisocyanatohexane (CAS 822-06-0)	TWA	0,035 mg/m3	Vapor and aerosol.
		0,005 ppm	Vapor and aerosol.

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value	Form
1-Methoxy-2-propyl acetate (CAS 108-65-6)	TWA	270 mg/m3	
Ethyl benzene (CAS 100-41-4)	TWA	50 ppm 88 mg/m3	
n-Butyl acetate (CAS 123-86-4)	TWA	20 ppm 480 mg/m3	
Toluene (CAS 108-88-3)	TWA	100 ppm 190 mg/m3	
Xylene (CAS 1330-20-7)	TWA	50 ppm 440 mg/m3 100 ppm	

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value	Form
1,6-Diisocyanatohexane (CAS 822-06-0)	AGW	0,035 mg/m3	Vapor and aerosol.
1-Methoxy-2-propyl acetate (CAS 108-65-6)	AGW	0,005 ppm 270 mg/m3	Vapor and aerosol.
Ethyl benzene (CAS 100-41-4)	AGW	50 ppm 88 mg/m3	
n-Butyl acetate (CAS 123-86-4)	AGW	20 ppm 300 mg/m3	
Toluene (CAS 108-88-3)	AGW	62 ppm 190 mg/m3	
Xylene (CAS 1330-20-7)	AGW	50 ppm 440 mg/m3 100 ppm	

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	STEL	0,15 mg/m3
	TWA	0,02 ppm 0,075 mg/m3 0,01 ppm
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	550 mg/m3
	TWA	100 ppm 275 mg/m3 50 ppm
Ethyl benzene (CAS 100-41-4)	STEL	545 mg/m3
	TWA	125 ppm 435 mg/m3 100 ppm
n-Butyl acetate (CAS 123-86-4)	STEL	950 mg/m3
	TWA	200 ppm 710 mg/m3 150 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m3
	TWA	100 ppm 192 mg/m3 50 ppm
Xylene (CAS 1330-20-7)	STEL	650 mg/m3
	TWA	150 ppm 435 mg/m3 100 ppm

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	STEL	0,035 mg/m3
	TWA	0,035 mg/m3
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	550 mg/m3
	TWA	275 mg/m3
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m3
	TWA	442 mg/m3
n-Butyl acetate (CAS 123-86-4)	STEL	950 mg/m3
	TWA	950 mg/m3
Toluene (CAS 108-88-3)	STEL	380 mg/m3
	TWA	190 mg/m3
Xylene (CAS 1330-20-7)	STEL	442 mg/m3
	TWA	221 mg/m3

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	STEL	0,07 mg/m3
	TWA	0,01 ppm 0,03 mg/m3 0,005 ppm
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	550 mg/m3
	TWA	100 ppm 275 mg/m3 50 ppm
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m3
	TWA	200 ppm 200 mg/m3 50 ppm
n-Butyl acetate (CAS 123-86-4)	TWA	700 mg/m3
	STEL	150 ppm
Toluene (CAS 108-88-3)	STEL	188 mg/m3 50 ppm
	TWA	94 mg/m3 25 ppm
Xylene (CAS 1330-20-7)	STEL	442 mg/m3 100 ppm
	TWA	109 mg/m3 25 ppm

Ireland. Occupational Exposure Limits

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	STEL	0,07 mg/m3
	TWA	0,005 ppm
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	550 mg/m3
	TWA	100 ppm 275 mg/m3 50 ppm
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m3
	TWA	200 ppm 442 mg/m3 100 ppm
n-Butyl acetate (CAS 123-86-4)	STEL	950 mg/m3
	TWA	200 ppm 710 mg/m3

Ireland. Occupational Exposure Limits Components

Type	Value
Toluene (CAS 108-88-3)	150 ppm 384 mg/m3
TWA	100 ppm 192 mg/m3
Xylene (CAS 1330-20-7)	50 ppm 442 mg/m3
TWA	100 ppm 221 mg/m3 50 ppm

Italy. Occupational Exposure Limits Components

Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	TWA 0,005 ppm
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL 550 mg/m3
TWA	100 ppm 275 mg/m3 50 ppm
Ethyl benzene (CAS 100-41-4)	STEL 884 mg/m3
TWA	200 ppm 442 mg/m3 100 ppm
n-Butyl acetate (CAS 123-86-4)	STEL 200 ppm
TWA	150 ppm
Toluene (CAS 108-88-3)	TWA 192 mg/m3 50 ppm
Xylene (CAS 1330-20-7)	STEL 442 mg/m3 100 ppm
TWA	221 mg/m3 50 ppm

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment Components

Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	TWA 0,05 mg/m3
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL 550 mg/m3
TWA	100 ppm 275 mg/m3 50 ppm
Ethyl benzene (CAS 100-41-4)	STEL 884 mg/m3
TWA	200 ppm 442 mg/m3 100 ppm
n-Butyl acetate (CAS 123-86-4)	TWA 200 mg/m3
Toluene (CAS 108-88-3)	STEL 150 mg/m3 40 ppm
TWA	50 mg/m3 14 ppm
Xylene (CAS 1330-20-7)	STEL 442 mg/m3 100 ppm
TWA	221 mg/m3 50 ppm

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components

Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	Ceiling 0,07 mg/m3
TWA	0,01 ppm 0,03 mg/m3

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	0,005 ppm 400 mg/m3
	TWA	75 ppm 250 mg/m3
Ethyl benzene (CAS 100-41-4)	STEL	50 ppm 884 mg/m3
	TWA	200 ppm 442 mg/m3
n-Butyl acetate (CAS 123-86-4)	STEL	100 ppm 700 mg/m3
	TWA	150 ppm 500 mg/m3
Toluene (CAS 108-88-3)	STEL	100 ppm 384 mg/m3
	TWA	192 mg/m3 50 ppm
Xylene (CAS 1330-20-7)	STEL	450 mg/m3 100 ppm
	TWA	200 mg/m3 50 ppm

Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A

Components	Type	Value
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	550 mg/m3
	TWA	100 ppm 275 mg/m3 50 ppm
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m3
	TWA	200 ppm 442 mg/m3 100 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m3 100 ppm
	TWA	192 mg/m3 50 ppm
Xylene (CAS 1330-20-7)	STEL	442 mg/m3 100 ppm
	TWA	221 mg/m3 50 ppm

Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)

Components	Type	Value
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	550 mg/m3
	TWA	100 ppm 275 mg/m3 50 ppm
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m3
	TWA	200 ppm 442 mg/m3 100 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m3 100 ppm
	TWA	192 mg/m3 50 ppm
Xylene (CAS 1330-20-7)	STEL	442 mg/m3

Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)

Components	Type	Value
	TWA	100 ppm 221 mg/m3 50 ppm

Netherlands. OELs (binding)

Components	Type	Value
1-Methoxy-2-propyl acetate (CAS 108-65-6)	TWA	550 mg/m3
Ethyl benzene (CAS 100-41-4)	STEL	430 mg/m3
Toluene (CAS 108-88-3)	TWA	215 mg/m3
	STEL	384 mg/m3
Xylene (CAS 1330-20-7)	TWA	150 mg/m3
	STEL	442 mg/m3
	TWA	210 mg/m3

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	STEL	0,01 ppm
	TLV	0,035 mg/m3 0,005 ppm
1-Methoxy-2-propyl acetate (CAS 108-65-6)	TLV	270 mg/m3
		50 ppm
Ethyl benzene (CAS 100-41-4)	TLV	20 mg/m3
		5 ppm
n-Butyl acetate (CAS 123-86-4)	TLV	355 mg/m3
		75 ppm
Toluene (CAS 108-88-3)	TLV	94 mg/m3
		25 ppm
Xylene (CAS 1330-20-7)	TLV	108 mg/m3
		25 ppm

Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	STEL	0,08 mg/m3
	TWA	0,04 mg/m3
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	520 mg/m3
	TWA	260 mg/m3
Ethyl benzene (CAS 100-41-4)	STEL	400 mg/m3
	TWA	200 mg/m3
n-Butyl acetate (CAS 123-86-4)	STEL	950 mg/m3
	TWA	200 mg/m3
Toluene (CAS 108-88-3)	STEL	200 mg/m3
	TWA	100 mg/m3
Xylene (CAS 1330-20-7)	TWA	100 mg/m3

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)

Components	Type	Value
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
	TWA	275 mg/m3 50 ppm
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m3
		200 ppm

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)

Components	Type	Value
Toluene (CAS 108-88-3)	TWA	442 mg/m3 100 ppm
	STEL	384 mg/m3 100 ppm
Xylene (CAS 1330-20-7)	TWA	192 mg/m3 50 ppm
	STEL	442 mg/m3 100 ppm
	TWA	221 mg/m3 50 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	TWA	0,005 ppm
Ethyl benzene (CAS 100-41-4)	STEL	125 ppm
n-Butyl acetate (CAS 123-86-4)	TWA	100 ppm
	STEL	200 ppm
Toluene (CAS 108-88-3)	TWA	150 ppm
	TWA	50 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	STEL	1 mg/m3
	TWA	0,14 ppm 0,05 mg/m3 0,007 ppm
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	550 mg/m3
	TWA	100 ppm 275 mg/m3 50 ppm
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m3
	TWA	200 ppm 442 mg/m3 100 ppm
n-Butyl acetate (CAS 123-86-4)	STEL	950 mg/m3
	TWA	200 ppm 715 mg/m3 150 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m3 100 ppm
	TWA	192 mg/m3 50 ppm
Xylene (CAS 1330-20-7)	STEL	442 mg/m3 100 ppm
	TWA	221 mg/m3 50 ppm

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	TWA	0,035 mg/m3
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	0,005 ppm 550 mg/m3
	TWA	100 ppm 275 mg/m3

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value
Ethyl benzene (CAS 100-41-4)	STEL	50 ppm 884 mg/m ³
	TWA	200 ppm 442 mg/m ³
n-Butyl acetate (CAS 123-86-4)	STEL	100 ppm 700 mg/m ³
	TWA	150 ppm 500 mg/m ³
Toluene (CAS 108-88-3)	STEL	100 ppm 384 mg/m ³
	TWA	100 ppm 192 mg/m ³
Xylene (CAS 1330-20-7)	STEL	50 ppm 442 mg/m ³
	TWA	100 ppm 221 mg/m ³ 50 ppm

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	TWA	0,035 mg/m ³
1-Methoxy-2-propyl acetate (CAS 108-65-6)	TWA	0,005 ppm 275 mg/m ³
Ethyl benzene (CAS 100-41-4)	TWA	50 ppm 442 mg/m ³
n-Butyl acetate (CAS 123-86-4)	TWA	100 ppm 480 mg/m ³
Toluene (CAS 108-88-3)	TWA	100 ppm 192 mg/m ³
Xylene (CAS 1330-20-7)	TWA	50 ppm 221 mg/m ³ 50 ppm

Spain. Occupational Exposure Limits

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	TWA	0,035 mg/m ³
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	0,005 ppm 550 mg/m ³
	TWA	100 ppm 275 mg/m ³
Ethyl benzene (CAS 100-41-4)	STEL	50 ppm 884 mg/m ³
	TWA	200 ppm 441 mg/m ³ 100 ppm
n-Butyl acetate (CAS 123-86-4)	STEL	965 mg/m ³
	TWA	200 ppm 724 mg/m ³ 150 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m ³ 100 ppm
	TWA	192 mg/m ³ 50 ppm
Xylene (CAS 1330-20-7)	STEL	442 mg/m ³

Spain. Occupational Exposure Limits Components**Type****Value**

TWA
100 ppm
221 mg/m3
50 ppm

Sweden. Occupational Exposure Limit Values Components**Type****Value**

1,6-Diisocyanatohexane (CAS 822-06-0)
Ceiling 0,03 mg/m3
TWA 0,005 ppm
0,02 mg/m3
0,002 ppm

1-Methoxy-2-propyl acetate (CAS 108-65-6)
STEL 400 mg/m3
TWA 75 ppm
250 mg/m3
50 ppm

Ethyl benzene (CAS 100-41-4)
STEL 450 mg/m3
TWA 100 ppm
200 mg/m3
50 ppm

n-Butyl acetate (CAS 123-86-4)
STEL 700 mg/m3
TWA 150 ppm
500 mg/m3
100 ppm

Toluene (CAS 108-88-3)
STEL 384 mg/m3
TWA 100 ppm
192 mg/m3
50 ppm

Xylene (CAS 1330-20-7)
STEL 442 mg/m3
TWA 100 ppm
221 mg/m3
50 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz Components**Type****Value**

1,6-Diisocyanatohexane (CAS 822-06-0)
STEL 0,02 mg/m3
TWA 0,02 mg/m3

1-Methoxy-2-propyl acetate (CAS 108-65-6)
STEL 275 mg/m3
TWA 50 ppm
275 mg/m3
50 ppm

Ethyl benzene (CAS 100-41-4)
STEL 220 mg/m3
TWA 50 ppm
220 mg/m3
50 ppm

n-Butyl acetate (CAS 123-86-4)
STEL 960 mg/m3
TWA 200 ppm
480 mg/m3
100 ppm

Toluene (CAS 108-88-3)
STEL 760 mg/m3
TWA 200 ppm
190 mg/m3
50 ppm

Xylene (CAS 1330-20-7)
STEL 870 mg/m3
TWA 200 ppm
435 mg/m3
100 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
1,6-Diisocyanatohexane (CAS 822-06-0)	STEL	0,07 mg/m ³
	TWA	0,02 mg/m ³
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	548 mg/m ³
	TWA	100 ppm 274 mg/m ³ 50 ppm
Ethyl benzene (CAS 100-41-4)	STEL	552 mg/m ³
	TWA	125 ppm 441 mg/m ³ 100 ppm
n-Butyl acetate (CAS 123-86-4)	STEL	966 mg/m ³
	TWA	200 ppm 724 mg/m ³ 150 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m ³
	TWA	100 ppm 191 mg/m ³ 50 ppm
Xylene (CAS 1330-20-7)	STEL	441 mg/m ³
	TWA	100 ppm 220 mg/m ³ 50 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Type	Value
1-Methoxy-2-propyl acetate (CAS 108-65-6)	STEL	550 mg/m ³
	TWA	100 ppm 275 mg/m ³ 50 ppm
Ethyl benzene (CAS 100-41-4)	STEL	884 mg/m ³
	TWA	200 ppm 442 mg/m ³ 100 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m ³
	TWA	100 ppm 192 mg/m ³ 50 ppm
Xylene (CAS 1330-20-7)	STEL	442 mg/m ³
	TWA	100 ppm 221 mg/m ³ 50 ppm

Biological limit values
Czech Republic. Limit Values for Indicators of Biological Exposure Tests in Urine and Blood, Annex 2, Tables 1 and 2, Government Decree 432/2003 Sb.

Components	Value	Determinant	Specimen	Sampling time
Ethyl benzene (CAS 100-41-4)	1100 µmol/mmol	Mandelic acid	Creatinine in urine	*
	1500 mg/g	Mandelic acid	Creatinine in urine	*
Toluene (CAS 108-88-3)	1000 µmol/mmol	Hippuric acid	Creatinine in urine	*
	1600 mg/g	Hippuric acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	820 µmol/mmol	Methylhippuric acids	Creatinine in urine	*
	1400 mg/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Finland. HTP-arvot, App 2., Biological Limit Values, (BRA/BGV) , Social Affairs and Ministry of Health

Components	Value	Determinant	Specimen	Sampling time
Ethyl benzene (CAS 100-41-4)	5,2 mmol/l	Mandelic acid	Urine	*
Toluene (CAS 108-88-3)	500 nmol/l	Toluene concentration	Blood	*
Xylene (CAS 1330-20-7)	5 mmol/l	Methylhippuric acids	Urine	*

* - For sampling details, please see the source document.

France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 2065)

Components	Value	Determinant	Specimen	Sampling time
Ethyl benzene (CAS 100-41-4)	1500 mg/g	Acide mandélique	Creatinine in urine	*
Toluene (CAS 108-88-3)	2500 mg/g	Acide hippurique	Creatinine in urine	*
	2500 mg/g	Acide hippurique	Creatinine in urine	*
	1 mg/l	Toluène	Venous blood	*
Xylene (CAS 1330-20-7)	1500 mg/g	Acides méthylhippuriques	Creatinine in urine	*

* - For sampling details, please see the source document.

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling time
1,6-Diisocyanatohexane (CAS 822-06-0)	15 µg/g	Hexamethylendiamin (nach Hydrolyse)	Creatinine in urine	*
Ethyl benzene (CAS 100-41-4)	300 mg/l	Mandelsäure plus Phenylglyoxylsäure	Urine	*
Toluene (CAS 108-88-3)	600 µg/l	Toluol	Blood	*
	1,5 mg/l	o-Kresol (nach Hydrolyse)	Urine	*
Xylene (CAS 1330-20-7)	2000 mg/l	Methylhippur-(Tolur-) säure (alle Isomere)	Urine	*
	1,5 mg/l	Xylol	Blood	*

* - For sampling details, please see the source document.

Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices

Components	Value	Determinant	Specimen	Sampling time
Ethyl benzene (CAS 100-41-4)	1500 mg/g	mandelic acid	Creatinine in urine	*
	1110 µmol/mmol	mandelic acid	Creatinine in urine	*
Toluene (CAS 108-88-3)	1 mg/g	o-crezol	Creatinine in urine	*
	1,05 µmol/mmol	o-crezol	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1500 mg/g	methyl hippuric acids	Creatinine in urine	*
	860 µmol/mmol	methyl hippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2

Components	Value	Determinant	Specimen	Sampling time
Ethyl benzene (CAS 100-41-4)	8,03 mg/g	2-ethylphenol	Creatinine in urine	*
	12 mg/l	2-ethylphenol	Urine	*
Toluene (CAS 108-88-3)	600 µg/l	Toluene	Blood	*
	1600 mg/g	Hippuric acid	Creatinine in urine	*

Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2

Components	Value	Determinant	Specimen	Sampling time
	1,03 mg/g	o-cresol (Phenol, 2-methyl-)	Creatinine in urine	*
	2401 mg/l	Hippuric acid	Urine	*
	1,5 mg/l	o-cresol (Phenol, 2-methyl-)	Urine	*
Xylene (CAS 1330-20-7)	1334 mg/g	Methylhippuric acids	Creatinine in urine	*
	2000 mg/l	Methylhippuric acids	Urine	*
	1,5 mg/l	Xylene	Blood	*

* - For sampling details, please see the source document.

Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4

Components	Value	Determinant	Specimen	Sampling time
Ethyl benzene (CAS 100-41-4)	700 mg/g	Suma del acido mandélico y el ácido fenilgloxílico	Creatinine in urine	*
Toluene (CAS 108-88-3)	1,6 g/g	Ácido hipúrico	Creatinine in urine	*
	0,5 mg/l	o-cresol (Phenol, 2-methyl-)	Urine	*
	0,05 mg/l	Tolueno	Blood	*
Xylene (CAS 1330-20-7)	1 g/g	Ácidos metilhipúricos	Creatinine in urine	*

* - For sampling details, please see the source document.

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Determinant	Specimen	Sampling time
1,6-Diisocyanatohexane (CAS 822-06-0)	15 µg/g	Hexamethylend iamin (nach Hydrolyse)	Creatinine in urine	*
Ethyl benzene (CAS 100-41-4)	800 mg/l	Mandelsäure plus Phenylglyoxyls äure	Urine	*
Toluene (CAS 108-88-3)	600 µg/l	Toluol	Blood	*
	2 g/g	Hippursäure	Creatinine in urine	*
	0,5 mg/l	o-Kresol	Urine	*
Xylene (CAS 1330-20-7)	1,5 g/g	Methyl-Hippurs äure	Creatinine in urine	*
	1,5 mg/l	Xylol	Blood	*

* - For sampling details, please see the source document.

UK. EH40 Biological Monitoring Guidance Values (BMGVs)

Components	Value	Determinant	Specimen	Sampling time
Xylene (CAS 1330-20-7)	650 mmol/mol	Methyl hippuric acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no-effect level (DNEL) Not available.

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines

EU Exposure Limit Values: Skin designation

1-Methoxy-2-propyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
Ethyl benzene (CAS 100-41-4)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.
Xylene (CAS 1330-20-7)	Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

- Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

- Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls

Inform appropriate managerial or supervisory personnel of all environmental releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid.

Form

Liquid.

Colour

Nearly colorless to. Light yellow.

Odour

Solvent.

Odour threshold

Not available.

pH

Not available.

Melting point/freezing point

-94,9 °C (-138,82 °F) estimated

Initial boiling point and boiling range

110,6 °C (231,08 °F) estimated

Flash point

4,4 °C (40,0 °F) estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

1,3 % estimated

Flammability limit - upper (%)

7,5 % estimated

Vapour pressure

21,48 hPa estimated

Vapour density

Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water)

Not available.

Solubility (other)

Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

425 °C (797 °F) estimated

Decomposition temperature

Not available.

Viscosity

Not available.

Explosive properties

Not available.

Oxidizing properties	Not available.
9.2. Other information	
Density	8,18 lbs/gal
Percent volatile	67,6 %
Specific gravity	0,98
VOC	5,5 lb/gal Material 5,5 lb/gal Regulatory 662 g/l Material 662 g/l Regulatory

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong acids. Strong oxidising agents. Nitrates. Halogens.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms Headache. May cause drowsiness and dizziness. Nausea, vomiting. Skin irritation. May cause redness and pain.

11.1. Information on toxicological effects

Acute toxicity Narcotic effects.

Components	Species	Test results
1,6-Diisocyanatohexane (CAS 822-06-0)		
Acute		
Dermal		
LD50	Rabbit	593 mg/kg
Inhalation		
LC50	Mouse	0,03 mg/l, 2 Hours
	Rat	40 mg/l, 1 Hours 22 mg/l, 4 Hours 0,385 mg/l, 6 Hours
Oral		
LD50	Mouse	1980 mg/kg
	Rat	960 mg/kg
Ethyl benzene (CAS 100-41-4)		
Acute		
Dermal		
LD50	Rabbit	17800 mg/kg
Oral		
LD50	Rat	3500 mg/kg

Components	Species	Test results
n-Butyl acetate (CAS 123-86-4)		
Acute		
Inhalation		
LC50	Wistar rat	160 mg/l, 4 Hours
Oral		
LD50	Rat	14000 mg/kg
Toluene (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	12124 mg/kg 14,1 ml/kg
Inhalation		
LC50	Mouse	5320 ppm, 8 Hours 400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours
Oral		
LD50	Rat	2,6 g/kg
Xylene (CAS 1330-20-7)		
Acute		
Dermal		
LD50	Rabbit	> 43 g/kg
Inhalation		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours
Oral		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory sensitisation	Due to partial or complete lack of data the classification is not possible.
Skin sensitisation	Due to partial or complete lack of data the classification is not possible.
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Ethyl benzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.
Mixture versus substance information	No information available.
Other information	May cause allergic respiratory and skin reactions.

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life with long lasting effects.

Components	Species		Test results
Ethyl benzene (CAS 100-41-4)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1,37 - 4,4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7,5 - 11 mg/l, 96 hours
n-Butyl acetate (CAS 123-86-4)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	17 - 19 mg/l, 96 hours
Toluene (CAS 108-88-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	5,46 - 9,83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch)	8,11 mg/l, 96 hours
Xylene (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7,711 - 9,591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

12.2. Persistence and degradability No data is available on the degradability of this product.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Ethyl benzene	3,15
n-Butyl acetate	1,78
Toluene	2,73
Xylene	3,12 - 3,2

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB assessment Not available.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint, Paint Related Material
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	33

Tunnel restriction code D/E
14.4. Packing group II
14.5. Environmental hazards Yes
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number UN1263
14.2. UN proper shipping name Paint, Paint Related Material
14.3. Transport hazard class(es)
Class 3
Subsidiary risk -
Label(s) 3
14.4. Packing group II
14.5. Environmental hazards Yes
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number UN1263
14.2. UN proper shipping name Paint, Paint Related Material
14.3. Transport hazard class(es)
Class 3
Subsidiary risk -
Label(s) 3
14.4. Packing group II
14.5. Environmental hazards Yes
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number UN1263
14.2. UN proper shipping name Paint, Paint Related Material
14.3. Transport hazard class(es)
Class 3
Subsidiary risk -
14.4. Packing group II
14.5. Environmental hazards Yes
ERG Code 3H
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed.
Cargo aircraft only Allowed.


IMDG

14.1. UN number UN1263
14.2. UN proper shipping name Paint, Paint Related Material
14.3. Transport hazard class(es)
Class 3
Subsidiary risk -
14.4. Packing group II
14.5. Environmental hazards
Marine pollutant Yes
EmS F-E, S-E
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I, as amended

Not listed.

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Ethyl benzene (CAS 100-41-4)

Toluene (CAS 108-88-3)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding, as amended

Toluene (CAS 108-88-3)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances

1,6-Diisocyanatohexane (CAS 822-06-0)

1-Methoxy-2-propyl acetate (CAS 108-65-6)

Ethyl benzene (CAS 100-41-4)
n-Butyl acetate (CAS 123-86-4)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended

1,6-Diisocyanatohexane (CAS 822-06-0)
1-Methoxy-2-propyl acetate (CAS 108-65-6)
Ethyl benzene (CAS 100-41-4)
n-Butyl acetate (CAS 123-86-4)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

Directive 94/33/EC on the protection of young people at work, as amended

1,6-Diisocyanatohexane (CAS 822-06-0)
Ethyl benzene (CAS 100-41-4)
Toluene (CAS 108-88-3)

Other regulations The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006. Pregnant women should not work with the product, if there is the least risk of exposure.

National regulations Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work. Follow national regulation for work with chemical agents.

15.2. Chemical safety assessment No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations Not available.

References Not available.

Information on evaluation method leading to the classification of mixture The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R10 Flammable.
R11 Highly flammable.
R20 Harmful by inhalation.
R20/21 Harmful by inhalation and in contact with skin.
R23 Toxic by inhalation.
R36/37/38 Irritating to eyes, respiratory system and skin.
R38 Irritating to skin.
R42/43 May cause sensitisation by inhalation and skin contact.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63 Possible risk of harm to the unborn child.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Revision information None.

Training information Follow training instructions when handling this material.

Disclaimer The information in the sheet was written based on the best knowledge and experience currently available. The information contained herein is based on data believed to be reliable and the manufacturer disclaims any liability incurred from the use or reliance upon the same. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a licence to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.