

1. Identification

Product identifier 2K SEALER ACTIVATOR - SLOW

Other means of identification

Product Code MA-122-H

Recommended use Automotive Refinish Hardener/Activator

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name VALSPAR Automotive

Address 600 Nova Drive SE
Massillon, Ohio 44646
United States

Telephone General Assistance 330-299-8879

Website www.valsparauto.com

E-mail RON.ANDRUS@valspar.com

Contact person Ronald Andrus

Emergency phone number CHEMTREC 800-424-9300

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Acute toxicity, inhalation	Category 3
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2B
	Sensitization, respiratory	Category 1
	Sensitization, skin	Category 1
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1B
Environmental hazards	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes eye irritation. Toxic if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause genetic defects. May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Call a poison center/doctor. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	45.63% of the mixture consists of component(s) of unknown acute inhalation toxicity.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2,6-Dimethyl-4-heptanone		108-83-8	20 to <30
homopolymer of HDI		28182-81-2	20 to <30
n-butyl acetate		123-86-4	1 to <5
light aromatic solvent naphtha		64742-95-6	0.1 to <1
Other components below reportable levels			40 to <50

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Dizziness. Headache. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2,6-Dimethyl-4-heptanone (CAS 108-83-8)	PEL	290 mg/m ³
n-butyl acetate (CAS 123-86-4)	PEL	50 ppm 710 mg/m ³
		150 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
2,6-Dimethyl-4-heptanone (CAS 108-83-8)	TWA	25 ppm
n-butyl acetate (CAS 123-86-4)	STEL	200 ppm
	TWA	150 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
2,6-Dimethyl-4-heptanone (CAS 108-83-8)	TWA	150 mg/m ³
		25 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
n-butyl acetate (CAS 123-86-4)	STEL	950 mg/m3
	TWA	200 ppm
		710 mg/m3 150 ppm

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	Wear positive pressure self-contained breathing apparatus (SCBA).
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties**Appearance**

Physical state	Liquid.
Form	Liquid.
Color	Clear colorless or nearly colorless

Odor Solvent.**Odor threshold** Not available.**pH** Not available.**Melting point/freezing point** -42.7 °F (-41.5 °C) estimated**Initial boiling point and boiling range** 282.74 °F (139.3 °C) estimated**Flash point** 116.0 °F (46.7 °C) estimated**Evaporation rate** Not available.**Flammability (solid, gas)** Not applicable.**Upper/lower flammability or explosive limits****Flammability limit - lower (%)** 0.8 % estimated**Flammability limit - upper (%)** 6.2 % estimated**Explosive limit - lower (%)** Not available.**Explosive limit - upper (%)** Not available.**Vapor pressure** 7.07 hPa estimated**Vapor density** Not available.**Relative density** Not available.**Solubility(ies)****Solubility (water)** Not available.

Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	745 °F (396.11 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	8.89 lbs/gal
Flammability class	Combustible II estimated
Percent volatile	73.36 %
Specific gravity	1.07
VOC	3 lb/gal Material 4.4 lb/gal Regulatory 355 g/l Material 521 g/l Regulatory

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Toxic if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Headache. Dizziness. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Toxic if inhaled. May cause an allergic skin reaction. May cause respiratory irritation.

Components	Species	Test Results
2,6-Dimethyl-4-heptanone (CAS 108-83-8)		
Acute		
Dermal		
LD50	Rabbit	16200 mg/kg
	Rat	> 2000 mg/kg
Inhalation		
LC50	Rat	> 5 mg/l, 4 Hours
Oral		
LD50	Mouse	1416 mg/kg
	Rat	5285 mg/kg
n-butyl acetate (CAS 123-86-4)		
Acute		
Inhalation		
LC50	Wistar rat	160 mg/l, 4 Hours

Components	Species	Test Results
Oral LD50	Rat	14000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes eye irritation.

Respiratory or skin sensitization

Respiratory sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure May cause respiratory irritation.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
n-butyl acetate (CAS 123-86-4)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 17 - 19 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

n-butyl acetate 1.78

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN1263

UN proper shipping name Paint, Paint Related Material
Transport hazard class(es)
Class 3
Subsidiary risk -
Label(s) 3
Packing group III
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Special provisions B1, B52, IB3, T4, TP1, TP29
Packaging exceptions 150
Packaging non bulk 203
Packaging bulk 242

IATA

UN number UN1263
UN proper shipping name Paint, Paint Related Material
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group III
Environmental hazards No.
ERG Code 3L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Other information
Passenger and cargo aircraft Allowed with restrictions.
Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1263
UN proper shipping name Paint, Paint Related Material
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group III
Environmental hazards
Marine pollutant No.
EmS F-E, S-E
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT





15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

n-butyl acetate (CAS 123-86-4) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

light aromatic solvent naphtha (CAS 64742-95-6)

US. Massachusetts RTK - Substance List

2,6-Dimethyl-4-heptanone (CAS 108-83-8)

n-butyl acetate (CAS 123-86-4)

US. New Jersey Worker and Community Right-to-Know Act

2,6-Dimethyl-4-heptanone (CAS 108-83-8)

n-butyl acetate (CAS 123-86-4)

US. Pennsylvania Worker and Community Right-to-Know Law

2,6-Dimethyl-4-heptanone (CAS 108-83-8)

n-butyl acetate (CAS 123-86-4)

US. Rhode Island RTK

n-butyl acetate (CAS 123-86-4)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision**Issue date** 10-23-2015**Version #** 01**HMIS® ratings** Health: 3*
Flammability: 3
Physical hazard: 0**NFPA ratings** Health: 3
Flammability: 3
Instability: 0**Disclaimer** The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.