

1. Identification

Product identifier **PREMIUM HARDENER - NORMAL**

Other means of identification

Product Code MH-005-H

Recommended use Automotive Refinish Hardener/Activator

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name	Quest Automotive Products	
Address	600 Nova Drive SE Massillon, OH 44646 United States	
Telephone	General Assistance	(330) 830-6000
E-mail	rpandrus@quest-ap.com	
Contact person	Ron Andrus	
Emergency phone number	CHEMTREC	(800) 424-9300

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, dermal	Category 4
	Acute toxicity, inhalation	Category 3
	Serious eye damage/eye irritation	Category 2B
	Sensitization, respiratory	Category 1
	Sensitization, skin	Category 1
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1B
Environmental hazards	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 3
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Harmful in contact with skin. May cause an allergic skin reaction. Causes eye irritation. Toxic if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Supplemental information	96.3% of the mixture consists of component(s) of unknown acute dermal toxicity. 26.59% of the mixture consists of component(s) of unknown acute inhalation toxicity. 57.19% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 56.88% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
homopolymer of HDI		28182-81-2	30 to <40
n-butyl acetate		123-86-4	30 to <40
1,2,4-Trimethylbenzene		95-63-6	1 to <5
light aromatic solvent naphtha		64742-95-6	1 to <5
Mesitylene		108-67-8	1 to <5
Cumene		98-82-8	0.1 to <1
Other components below reportable levels			20 to <30

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Difficulty in breathing. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Carbon dioxide (CO ₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.
----------------------------------	--

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.
--------------------------------------	---

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Cumene (CAS 98-82-8)	PEL	245 mg/m3 50 ppm
n-butyl acetate (CAS 123-86-4)	PEL	710 mg/m3 150 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	25 ppm
Cumene (CAS 98-82-8)	TWA	50 ppm
Mesitylene (CAS 108-67-8)	TWA	25 ppm
n-butyl acetate (CAS 123-86-4)	STEL	200 ppm
	TWA	150 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3 25 ppm
Cumene (CAS 98-82-8)	TWA	245 mg/m3 50 ppm
Mesitylene (CAS 108-67-8)	TWA	125 mg/m3 25 ppm
n-butyl acetate (CAS 123-86-4)	STEL	950 mg/m3 200 ppm
	TWA	710 mg/m3 150 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines**US - California OELs: Skin designation**

Cumene (CAS 98-82-8) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Cumene (CAS 98-82-8) Skin designation applies.

US - Tennessee OELs: Skin designation

Cumene (CAS 98-82-8) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Cumene (CAS 98-82-8) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Cumene (CAS 98-82-8) Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	Wear positive pressure self-contained breathing apparatus (SCBA).
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance	Liquid.
Physical state	Liquid.
Form	Liquid.
Color	Clear colorless or nearly colorless
Odor	Solvent.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-108.4 °F (-78 °C) estimated
Initial boiling point and boiling range	258.98 °F (126.1 °C) estimated
Flash point	71.6 °F (22.0 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.4 % estimated
Flammability limit - upper (%)	7.5 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	15.33 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	797 °F (425 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	8.44 lbs/gal
Flammability class	Flammable IB estimated
Percent volatile	53.61 %
Specific gravity	1.01
VOC	3.9231920460460228 lbs/gal Material 3.9231920460460228 lbs/gal Regulatory 470.11610287769491 g/l Material 470.11610287769491 g/l Regulatory

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Nitrates.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Toxic if inhaled. May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	Harmful in contact with skin. May cause an allergic skin reaction.
Eye contact	Causes eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Headache. May cause drowsiness and dizziness. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Difficulty in breathing. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Toxic if inhaled. Harmful in contact with skin. Narcotic effects. May cause an allergic skin reaction.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg
Inhalation		
LC50	Rat	> 2000 ppm, 48 Hours
Oral		
LD50	Rat	6 g/kg
Cumene (CAS 98-82-8)		
Acute		
Inhalation		
LC50	Mouse	2000 ppm, 7 Hours 24.7 mg/l, 2 Hours
	Rat	8000 ppm, 4 Hours
Oral		
LD50	Rat	1400 mg/kg
Mesitylene (CAS 108-67-8)		
Acute		
Oral		
LD50	Rat	8970 mg/kg
n-butyl acetate (CAS 123-86-4)		
Acute		
Inhalation		
LC50	Wistar rat	160 mg/l, 4 Hours
Oral		
LD50	Rat	14000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Causes eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	May cause genetic defects.
Carcinogenicity	May cause cancer.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Cumene (CAS 98-82-8)	2B Possibly carcinogenic to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 7.19 - 8.28 mg/l, 96 hours
Cumene (CAS 98-82-8)		
Aquatic		
Crustacea	EC50	Brine shrimp (<i>Artemia</i> sp.) 3.55 - 11.29 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>) 2.7 mg/l, 96 hours
Mesitylene (CAS 108-67-8)		
Aquatic		
Fish	LC50	Goldfish (<i>Carassius auratus</i>) 9.89 - 15.05 mg/l, 96 hours
n-butyl acetate (CAS 123-86-4)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 17 - 19 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Cumene	3.66
n-butyl acetate	1.78

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1263
UN proper shipping name	Paint, Paint Related Material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB2, T7, TP1, TP8, TP28
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242

IATA

UN number	UN1263
UN proper shipping name	Paint, Paint Related Material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3H
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1263
UN proper shipping name	Paint, Paint Related Material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Cumene (CAS 98-82-8) Listed.
n-butyl acetate (CAS 123-86-4) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2,4-Trimethylbenzene	95-63-6	1 to <5
Cumene	98-82-8	0.1 to <1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Cumene (CAS 98-82-8)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-Trimethylbenzene (CAS 95-63-6)
Cumene (CAS 98-82-8)
light aromatic solvent naphtha (CAS 64742-95-6)
Mesitylene (CAS 108-67-8)

US. Massachusetts RTK - Substance List

1,2,4-Trimethylbenzene (CAS 95-63-6)
Cumene (CAS 98-82-8)
Mesitylene (CAS 108-67-8)
n-butyl acetate (CAS 123-86-4)

US. New Jersey Worker and Community Right-to-Know Act

1,2,4-Trimethylbenzene (CAS 95-63-6)
Cumene (CAS 98-82-8)
Mesitylene (CAS 108-67-8)
n-butyl acetate (CAS 123-86-4)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2,4-Trimethylbenzene (CAS 95-63-6)
Cumene (CAS 98-82-8)
Mesitylene (CAS 108-67-8)
n-butyl acetate (CAS 123-86-4)

US. Rhode Island RTK

1,2,4-Trimethylbenzene (CAS 95-63-6)
Cumene (CAS 98-82-8)
n-butyl acetate (CAS 123-86-4)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Cumene (CAS 98-82-8) Listed: April 6, 2010

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-01-2015
Version #	01
HMIS® ratings	Health: 3* Flammability: 3 Physical hazard: 0
NFPA ratings	Health: 3 Flammability: 3 Instability: 0

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.

Revision Information

Product and Company Identification: Alternate Trade Names