

## 1. Identification

**Product identifier** 2.1 VOC DTM Primer - Gray

**Other means of identification**

**Product Code** MP-220-QT

**Recommended use** Automotive Refinish Primer

**Manufacturer/Importer/Supplier/Distributor information**

**Company name** VALSPAR Automotive

**Address**  
600 Nova Drive SE  
Massillon, Ohio 44646  
United States

**Telephone** General Assistance 330-299-8879

**Website** www.valsparauto.com

**E-mail** RON.ANDRUS@valspar.com

**Contact person** Ronald Andrus

**Emergency phone number** CHEMTREC 800-424-9300

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 3
<b>Health hazards</b>	Acute toxicity, oral	Category 4
	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Carcinogenicity	Category 2
	Reproductive toxicity (the unborn child)	Category 2
<b>Environmental hazards</b>	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 3
<b>OSHA defined hazards</b>	Not classified.	

**Label elements**



**Signal word** Warning

**Hazard statement** Flammable liquid and vapor. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. Suspected of causing cancer. Suspected of damaging the unborn child. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

**Precautionary statement**

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

<b>Response</b>	If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
<b>Storage</b>	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	85.29% of the mixture consists of component(s) of unknown acute oral toxicity. 87.53% of the mixture consists of component(s) of unknown acute inhalation toxicity. 57.81% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 81.16% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
4-Chlorobenzotrifluoride		98-56-6	20 to <30
barium sulfate		7727-43-7	10 to <20
Calcium carbonate		1317-65-3	10 to <20
Talc		14807-96-6	10 to <20
2-Heptanone		110-43-0	5 to <10
acetone		67-64-1	1 to <5
Kaolin		1332-58-7	1 to <5
Titanium dioxide		13463-67-7	1 to <5
1,2-Dimethylbenzene		95-47-6	0.1 to <1
Ethyl benzene		100-41-4	0.1 to <1
Other components below reportable levels			10 to <20

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.
<b>Most important symptoms/effects, acute and delayed</b>	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

**Suitable extinguishing media** Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Flammable liquid and vapor.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

**Precautions for safe handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not taste or swallow. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities** Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
1,2-Dimethylbenzene (CAS 95-47-6)	PEL	435 mg/m3	
2-Heptanone (CAS 110-43-0)	PEL	100 ppm	
		465 mg/m3	
		100 ppm	

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm	
barium sulfate (CAS 7727-43-7)	PEL	5 mg/m3	Respirable fraction.
Calcium carbonate (CAS 1317-65-3)	PEL	15 mg/m3 5 mg/m3	Total dust. Respirable fraction.
Ethyl benzene (CAS 100-41-4)	PEL	15 mg/m3 435 mg/m3	Total dust.
Kaolin (CAS 1332-58-7)	PEL	100 ppm 5 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3 15 mg/m3	Total dust. Total dust.

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

Components	Type	Value	Form
Talc (CAS 14807-96-6)	TWA	0.3 mg/m3 0.1 mg/m3 20 mppcf 2.4 mppcf	Total dust. Respirable. Respirable.

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
1,2-Dimethylbenzene (CAS 95-47-6)	STEL	150 ppm	
	TWA	100 ppm	
2-Heptanone (CAS 110-43-0)	TWA	50 ppm	
acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
barium sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
Ethyl benzene (CAS 100-41-4)	TWA	20 ppm	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
1,2-Dimethylbenzene (CAS 95-47-6)	STEL	655 mg/m3	
	TWA	150 ppm 435 mg/m3 100 ppm	
2-Heptanone (CAS 110-43-0)	TWA	465 mg/m3	
acetone (CAS 67-64-1)	TWA	100 ppm 590 mg/m3 250 ppm	
barium sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable.
Calcium carbonate (CAS 1317-65-3)	TWA	10 mg/m3 5 mg/m3	Total Respirable.
		10 mg/m3	Total

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
Ethyl benzene (CAS 100-41-4)	STEL	545 mg/m <sup>3</sup>	
		125 ppm	
	TWA	435 mg/m <sup>3</sup>	
Kaolin (CAS 1332-58-7)	TWA	100 ppm	Respirable.
		5 mg/m <sup>3</sup>	Total
Talc (CAS 14807-96-6)	TWA	10 mg/m <sup>3</sup>	Respirable.
		2 mg/m <sup>3</sup>	

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
1,2-Dimethylbenzene (CAS 95-47-6)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Ethyl benzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance****Physical state**

Liquid.

**Form**

Liquid.

**Color**

Grey Opaque.

**Odor**

Solvent.

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point/freezing point**

-31.9 °F (-35.5 °C) estimated

**Initial boiling point and boiling range**

282.74 °F (139.3 °C) estimated

**Flash point**

102.0 °F (38.9 °C) estimated

**Evaporation rate**

Not available.

**Flammability (solid, gas)**

Not applicable.

## Upper/lower flammability or explosive limits

<b>Flammability limit - lower (%)</b>	1.1 % estimated
<b>Flammability limit - upper (%)</b>	7.9 % estimated
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	4.81 hPa estimated
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	740 °F (393.33 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	13.86 lbs/gal
<b>Explosive properties</b>	Not explosive.
<b>Flammability class</b>	Combustible II estimated
<b>Oxidizing properties</b>	Not oxidizing.
<b>Percent volatile</b>	34.4 %
<b>Specific gravity</b>	1.66
<b>VOC</b>	1.2 lbs/gal Material 1.9 lbs/gal Regulatory 149 g/l Material 223 g/l Regulatory

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong acids. Aluminum. Phosphorus. Fluorine.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Harmful if inhaled.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Harmful if swallowed.

**Symptoms related to the physical, chemical and toxicological characteristics** Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

### Information on toxicological effects

**Acute toxicity** Harmful if inhaled. Harmful if swallowed. May cause respiratory irritation.

Components	Species	Test Results
1,2-Dimethybenzene (CAS 95-47-6)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	> 43 g/kg
<b>Inhalation</b>		
LC50	Mouse	4600 ppm, 6 Hours
	Rat	6350 ppm, 4 Hours
<b>Oral</b>		
LD50	Mouse	1590 mg/kg
	Rat	4300 mg/kg
2-Heptanone (CAS 110-43-0)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	12600 mg/kg
<b>Oral</b>		
LD50	Mouse	730 mg/kg
	Rat	1.67 g/kg
acetone (CAS 67-64-1)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	20000 mg/kg 20 ml/kg
<b>Inhalation</b>		
LC50	Rat	76 mg/l, 4 Hours 50.1 mg/l, 8 Hours
<b>Oral</b>		
LD50	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
Ethyl benzene (CAS 100-41-4)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	17800 mg/kg
<b>Oral</b>		
LD50	Rat	3500 mg/kg
Kaolin (CAS 1332-58-7)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rat	> 5000 mg/kg
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** Suspected of causing cancer.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

1,2-Dimethylbenzene (CAS 95-47-6)	3 Not classifiable as to carcinogenicity to humans.
Ethyl benzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not regulated.

**US. National Toxicology Program (NTP) Report on Carcinogens**

Not listed.

**Reproductive toxicity** Suspected of damaging the unborn child.

**Specific target organ toxicity - single exposure** May cause respiratory irritation.

**Specific target organ toxicity - repeated exposure** Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

**12. Ecological information**

**Ecotoxicity** Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
1,2-Dimethylbenzene (CAS 95-47-6)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	0.78 - 2.51 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	5.59 - 11.6 mg/l, 96 hours
2-Heptanone (CAS 110-43-0)			
<b>Aquatic</b>			
Fish	LC50	Fathead minnow (Pimephales promelas)	126 - 137 mg/l, 96 hours
acetone (CAS 67-64-1)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
barium sulfate (CAS 7727-43-7)			
<b>Aquatic</b>			
Crustacea	EC50	Tubificid worm (Tubifex tubifex)	28.61 - 38.03 mg/l, 48 hours
Ethyl benzene (CAS 100-41-4)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours
Titanium dioxide (CAS 13463-67-7)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

1,2-Dimethylbenzene	3.12
2-Heptanone	1.98
acetone	-0.24



**Partition coefficient n-octanol / water (log Kow)**

Ethyl benzene

3.15

**Mobility in soil**

No data available.

**Other adverse effects**

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal considerations****Disposal instructions**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations**

Dispose in accordance with all applicable regulations.

**Hazardous waste code**

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products**

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging**

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. Transport information****DOT****UN number**

UN1263

**UN proper shipping name**

UN1263, Paint Related Material

**Transport hazard class(es)****Class**

3

**Subsidiary risk**

-

**Label(s)**

3

**Packing group**

III

**Special precautions for user**

Read safety instructions, SDS and emergency procedures before handling.

**Special provisions**

B1, B52, IB3, T4, TP1, TP29

**Packaging exceptions**

150

**Packaging non bulk**

203

**Packaging bulk**

242

**IATA****UN number**

UN1263

**UN proper shipping name**

Paint Related Material

**Transport hazard class(es)****Class**

3

**Subsidiary risk**

-

**Packing group**

III

**Environmental hazards**

No.

**ERG Code**

3L

**Special precautions for user**

Read safety instructions, SDS and emergency procedures before handling.

**Other information****Passenger and cargo aircraft**

Allowed with restrictions.

**Cargo aircraft only**

Allowed with restrictions.

**IMDG****UN number**

UN1263

**UN proper shipping name**

Paint Related Material

**Transport hazard class(es)****Class**

3

**Subsidiary risk**

-

**Packing group**

III

**Environmental hazards****Marine pollutant**

No.

**EmS**

F-E, S-E

**Special precautions for user**

Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

DOT



IATA; IMDG



## 15. Regulatory information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

4-Chlorobenzotrifluoride (CAS 98-56-6) 1.0 % One-Time Export Notification only.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

1,2-Dimethybenzene (CAS 95-47-6) Listed.  
acetone (CAS 67-64-1) Listed.  
barium sulfate (CAS 7727-43-7) Listed.  
Ethyl benzene (CAS 100-41-4) Listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

#### SARA 311/312 Hazardous chemical

No

#### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2-Dimethybenzene	95-47-6	0.1 to <1
Ethyl benzene	100-41-4	0.1 to <1

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

1,2-Dimethybenzene (CAS 95-47-6)  
Ethyl benzene (CAS 100-41-4)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

acetone (CAS 67-64-1) 6532

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

acetone (CAS 67-64-1) 35 %WV

**DEA Exempt Chemical Mixtures Code Number**

acetone (CAS 67-64-1) 6532

**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

2-Heptanone (CAS 110-43-0) Other Flavoring Substances with OSHA PEL's  
acetone (CAS 67-64-1) Low priority

**US state regulations**

**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

1,2-Dimethylbenzene (CAS 95-47-6)  
acetone (CAS 67-64-1)  
Ethyl benzene (CAS 100-41-4)  
Talc (CAS 14807-96-6)  
Titanium dioxide (CAS 13463-67-7)

**US. Massachusetts RTK - Substance List**

1,2-Dimethylbenzene (CAS 95-47-6)  
2-Heptanone (CAS 110-43-0)  
acetone (CAS 67-64-1)  
barium sulfate (CAS 7727-43-7)  
Calcium carbonate (CAS 1317-65-3)  
Ethyl benzene (CAS 100-41-4)  
Kaolin (CAS 1332-58-7)  
Talc (CAS 14807-96-6)  
Titanium dioxide (CAS 13463-67-7)

**US. New Jersey Worker and Community Right-to-Know Act**

1,2-Dimethylbenzene (CAS 95-47-6)  
2-Heptanone (CAS 110-43-0)  
4-Chlorobenzotrifluoride (CAS 98-56-6)  
acetone (CAS 67-64-1)  
barium sulfate (CAS 7727-43-7)  
Calcium carbonate (CAS 1317-65-3)  
Ethyl benzene (CAS 100-41-4)  
Kaolin (CAS 1332-58-7)  
Talc (CAS 14807-96-6)  
Titanium dioxide (CAS 13463-67-7)

**US. Pennsylvania Worker and Community Right-to-Know Law**

1,2-Dimethylbenzene (CAS 95-47-6)  
2-Heptanone (CAS 110-43-0)  
acetone (CAS 67-64-1)  
barium sulfate (CAS 7727-43-7)  
Calcium carbonate (CAS 1317-65-3)  
Ethyl benzene (CAS 100-41-4)  
Kaolin (CAS 1332-58-7)  
Talc (CAS 14807-96-6)  
Titanium dioxide (CAS 13463-67-7)

**US. Rhode Island RTK**

1,2-Dimethylbenzene (CAS 95-47-6)  
acetone (CAS 67-64-1)  
Ethyl benzene (CAS 100-41-4)

## US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon Black (CAS 1333-86-4)	Listed: February 21, 2003
Ethyl benzene (CAS 100-41-4)	Listed: June 11, 2004
Silicon dioxide (CAS 14808-60-7)	Listed: October 1, 1988
Titanium dioxide (CAS 13463-67-7)	Listed: September 2, 2011

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

<b>Issue date</b>	12-21-2015
<b>Revision date</b>	03-22-2016
<b>Version #</b>	02
<b>HMIS® ratings</b>	Health: 2* Flammability: 3 Physical hazard: 0
<b>NFPA ratings</b>	Health: 2 Flammability: 3 Instability: 0
<b>Disclaimer</b>	The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.
<b>Revision information</b>	This document has undergone significant changes and should be reviewed in its entirety.